



DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 1207	12.0 ± 0.3	12.0 ± 0.3	8.0 Max.	2.90	7.00	5.40

SERIES LIST

No.	Part No.	L (μH)	Test Frequency (KHz)	RDC Max. ()	IDC Max. (A)
1	JPRH 1207-1R0M -	1.0	100	0.0065	14.00
2	JPRH 1207-2R4M -	2.4	100	0.0105	10.30
3	JPRH 1207-3R5M -	3.5	100	0.0124	9.30
4	JPRH 1207-4R6M -	4.6	100	0.0138	9.10
5	JPRH 1207-5R8M -	5.8	100	0.0162	8.60
6	JPRH 1207-7R4M -	7.4	100	0.0177	7.40
7	JPRH 1207-100M -	10	1	0.0195	6.70
8	JPRH 1207-120M -	12	1	0.0213	6.45
9	JPRH 1207-150M -	15	1	0.0264	5.65
10	JPRH 1207-180M -	18	1	0.0280	5.10
11	JPRH 1207-220M -	22	1	0.0364	4.70
12	JPRH 1207-270M -	27	1	0.0416	4.20
13	JPRH 1207-330M -	33	1	0.0533	3.90
14	JPRH 1207-390M -	39	1	0.0605	3.50
15	JPRH 1207-470M -	47	1	0.0780	3.25
16	JPRH 1207-560M -	56	1	0.0900	2.90
17	JPRH 1207-680M -	68	1	0.1200	2.60
18	JPRH 1207-820M -	82	1	0.1190	2.40
19	JPRH 1207-101M -	100	1	0.1510	2.10
20	JPRH 1207-121M -	120	1	0.1690	1.90
21	JPRH 1207-151M -	150	1	0.2270	1.80
22	JPRH 1207-181M -	180	1	0.2990	1.55
23	JPRH 1207-221M -	220	1	0.3380	1.45
24	JPRH 1207-271M -	270	1	0.4190	1.30
25	JPRH 1207-331M -	330	1	0.4710	1.20
26	JPRH 1207-391M -	390	1	0.5720	1.10
27	JPRH 1207-471M -	470	1	0.7410	1.00
28	JPRH 1207-561M -	560	1	0.8520	0.95
29	JPRH 1207-681M -	680	1	1.1300	0.85
30	JPRH 1207-821M -	820	1	1.2400	0.75
31	JPRH 1207-102M -	1000	1	1.5000	0.70

Tolerance : M ± 20% , M tolerance is standard.

: Revision of specification

PACKAGE

Type	JPRH 1207
Q'TY/Reel	500