

## Surface Mount Glass Passivated Ultrafast Rectifier

**SUPERECTIFIER®**

**DO-213AB (GL41)**
**FEATURES**

- Superectifier structure for high reliability condition
- Cavity-free glass-passivated junction
- Ideal for automated placement
- Ultrafast reverse recovery time
- Low switching losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 250 °C
- AEC-Q101 qualified
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

**TYPICAL APPLICATIONS**

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.

PRIMARY CHARACTERISTICS	
$I_{F(AV)}$	1.0 A
$V_{RRM}$	50 V to 400 V
$I_{FSM}$	30 A
$t_{rr}$	50 ns
$V_F$	1.0 V, 1.25 V
$T_J$ max.	175 °C
Package	DO-213AB (GL41)
Diode variations	Single die

**MECHANICAL DATA**

**Case:** DO-213AB, molded epoxy over glass body  
Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS-compliant, commercial grade  
Base P/NHE3 - RoHS-compliant, AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102  
E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

**Polarity:** Two bands indicate cathode end - 1<sup>st</sup> band denotes device type and 2<sup>nd</sup> band denotes repetitive peak reverse voltage rating

MAXIMUM RATINGS ( $T_A = 25\text{ °C}$ unless otherwise noted)								
PARAMETER	SYMBOL	BYM12-50	BYM12-100	BYM12-150	BYM12-200	BYM12-300	BYM12-400	UNIT
		EGL41A	EGL41B	EGL41C	EGL41D	EGL41F	EGL41G	
Polarity color bands (2 <sup>nd</sup> band)		Gray	Red	Pink	Orange	Brown	Yellow	
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	150	200	300	400	V
Maximum RMS voltage	$V_{RMS}$	35	70	105	140	210	280	V
Maximum DC blocking voltage	$V_{DC}$	50	100	150	200	300	400	V
Maximum average forward rectified current at $T_T = 75\text{ °C}$	$I_{F(AV)}$	1.0						A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	30						A
Operating junction and storage temperature range	$T_J, T_{STG}$	- 65 to + 175						°C



<b>ELECTRICAL CHARACTERISTICS</b> ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)									
PARAMETER	TEST CONDITIONS	SYMBOL	BYM12-50	BYM12-100	BYM12-150	BYM12-200	BYM12-300	BYM12-400	UNIT
			EGL41A	EGL41B	EGL41C	EGL41D	EGL41F	EGL41G	
Max. instantaneous forward voltage	1.0 A	$V_F^{(1)}$	1.0				1.25		V
Max. DC reverse current at rated DC blocking voltage	$T_A = 25\text{ }^\circ\text{C}$	$I_R^{(1)}$	5.0						$\mu\text{A}$
	$T_A = 125\text{ }^\circ\text{C}$		50						
Max. reverse recovery time	$I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ , $t_{rr} = 0.25\text{ A}$	$t_{rr}$	50						ns
Typical junction capacitance	4.0 V, 1 MHz	$C_J$	20				14		pF

**Note**

(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle

<b>THERMAL CHARACTERISTICS</b> ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)									
PARAMETER	SYMBOL	BYM12-50	BYM12-100	BYM12-150	BYM12-200	BYM12-300	BYM12-400	UNIT	
		EGL41A	EGL41B	EGL41C	EGL41D	EGL41F	EGL41G		
Maximum thermal resistance	$R_{\theta JA}^{(1)}$	60						$^\circ\text{C/W}$	
	$R_{\theta JT}^{(2)}$	30							

**Notes**

- (1) Thermal resistance from junction to ambient, 0.24" x 0.24" (6.0 mm x 6.0 mm) copper pads to each terminal
- (2) Thermal resistance from junction to terminal, 0.24" x 0.24" (6.0 mm x 6.0 mm) copper pads to each terminal

<b>ORDERING INFORMATION</b> (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
EGL41D-E3/96	0.114	96	1500	7" diameter plastic tape and reel
EGL41D-E3/97	0.114	97	5000	13" diameter plastic tape and reel
EGL41DHE3/96 <sup>(1)</sup>	0.114	96	1500	7" diameter plastic tape and reel
EGL41DHE3/97 <sup>(1)</sup>	0.114	97	5000	13" diameter plastic tape and reel

**Note**

(1) AEC-Q101 qualified

**RATINGS AND CHARACTERISTICS CURVES** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Fig. 1 - Maximum Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Leakage Characteristics





Fig. 6 - Typical Transient Thermal Impedance


**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)

**DO-213AB (GL41)**



1<sup>st</sup> Band Denotes Type and Positive End (Cathode)

**Mounting Pad Layout**





## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Vishay:

[BYM12-100/76](#) [BYM12-100-E3/51](#) [BYM12-100-E3/75](#) [BYM12-100-E3/76](#) [BYM12-100-E3/96](#) [BYM12-100-E3/97](#)  
[BYM12-100HE3/75](#) [BYM12-100HE3/76](#) [BYM12-100HE3/96](#) [BYM12-100HE3/97](#) [BYM12-150/76](#) [BYM12-150-E3/51](#)  
[BYM12-150-E3/75](#) [BYM12-150-E3/76](#) [BYM12-150-E3/96](#) [BYM12-150-E3/97](#) [BYM12-150HE3/75](#) [BYM12-150HE3/76](#)  
[BYM12-150HE3/96](#) [BYM12-150HE3/97](#) [BYM12-200-E3/75](#) [BYM12-200-E3/76](#) [BYM12-200-E3/96](#) [BYM12-200-](#)  
[E3/97](#) [BYM12-200HE3/75](#) [BYM12-200HE3/76](#) [BYM12-200HE3/96](#) [BYM12-200HE3/97](#) [BYM12-300/76](#) [BYM12-300-](#)  
[E3/75](#) [BYM12-300-E3/76](#) [BYM12-300-E3/96](#) [BYM12-300-E3/97](#) [BYM12-300HE3/75](#) [BYM12-300HE3/76](#) [BYM12-](#)  
[300HE3/96](#) [BYM12-300HE3/97](#) [BYM12-400/76](#) [BYM12-400-E3/75](#) [BYM12-400-E3/76](#) [BYM12-400-E3/96](#) [BYM12-](#)  
[400-E3/97](#) [BYM12-400HE3/75](#) [BYM12-400HE3/76](#) [BYM12-400HE3/96](#) [BYM12-400HE3/97](#) [BYM12-50/76](#) [BYM12-](#)  
[50-E3/75](#) [BYM12-50-E3/76](#) [BYM12-50-E3/96](#) [BYM12-50-E3/97](#) [BYM12-50HE3/75](#) [BYM12-50HE3/76](#) [BYM12-](#)  
[50HE3/96](#) [BYM12-50HE3/97](#) [EGL41A-E3/51](#) [EGL41A-E3/75](#) [EGL41A-E3/76](#) [EGL41A-E3/96](#) [EGL41A-E3/97](#)  
[EGL41AHE3/75](#) [EGL41AHE3/76](#) [EGL41AHE3/96](#) [EGL41AHE3/97](#) [EGL41B/46](#) [EGL41B-E3/51](#) [EGL41B-E3/75](#)  
[EGL41B-E3/76](#) [EGL41B-E3/96](#) [EGL41B-E3/97](#) [EGL41BHE3/75](#) [EGL41BHE3/76](#) [EGL41BHE3/96](#) [EGL41BHE3/97](#)  
[EGL41C-E3/75](#) [EGL41C-E3/76](#) [EGL41C-E3/96](#) [EGL41C-E3/97](#) [EGL41CHE3/75](#) [EGL41CHE3/76](#) [EGL41CHE3/96](#)  
[EGL41CHE3/97](#) [EGL41D/46](#) [EGL41D-E3/51](#) [EGL41D-E3/75](#) [EGL41D-E3/76](#) [EGL41D-E3/96](#) [EGL41D-E3/97](#)  
[EGL41DHE3/75](#) [EGL41DHE3/76](#) [EGL41DHE3/96](#) [EGL41DHE3/97](#) [EGL41F-E3/75](#) [EGL41F-E3/76](#) [EGL41F-E3/96](#)  
[EGL41F-E3/97](#) [EGL41FHE3/75](#) [EGL41FHE3/76](#) [EGL41FHE3/96](#) [EGL41FHE3/97](#)