





- ▼ Lower Gate Charge
- ▼ Simple Drive Requirement
- ▼ Fast Switching Characteristic
- ▼ RoHS Compliant & Halogen-Free



$BV_{DSS}$	-100V
$R_{DS(ON)}$	80mΩ
$I_D^3$	-25A

## Description

AP30P10 series are from Advanced Power innovative design and silicon process technology to achieve the lowest possible on-resistance and fast switching performance. It provides the designer with an extreme efficient device for use in a wide range of power applications. The TO-220CFM package is widely preferred for all commercial-industrial through hole applications. The mold compound provides a high isolation voltage capability and low thermal resistance between the tab and the external heat-sink.



TO-220CFM(I)

## Absolute Maximum Ratings@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	-100	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D @ T_c = 25^\circ\text{C}$	Drain Current <sup>3</sup> , $V_{GS} @ 10\text{V}$	-25	A
$I_D @ T_c = 100^\circ\text{C}$	Drain Current <sup>3</sup> , $V_{GS} @ 10\text{V}$	-15	A
$I_{DM}$	Pulsed Drain Current <sup>1</sup>	-80	A
$P_D @ T_c = 25^\circ\text{C}$	Total Power Dissipation	31.3	W
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_j$	Operating Junction Temperature Range	-55 to 150	°C

## Thermal Data

Symbol	Parameter	Value	Units
$R_{thj-c}$	Maximum Thermal Resistance, Junction-case	4	°C/W
$R_{thj-a}$	Maximum Thermal Resistance, Junction-ambient	65	°C/W



## Electrical Characteristics @ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=-1\text{mA}$	-100	-	-	V
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{\text{GS}}=-10\text{V}, I_{\text{D}}=-12\text{A}$	-	-	80	$\text{m}\Omega$
		$V_{\text{GS}}=-4.5\text{V}, I_{\text{D}}=-8\text{A}$	-	-	100	$\text{m}\Omega$
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=-250\text{\mu A}$	-1	-	-3	V
$g_{\text{fs}}$	Forward Transconductance	$V_{\text{DS}}=-10\text{V}, I_{\text{D}}=-12\text{A}$	-	23	-	S
$I_{\text{DSS}}$	Drain-Source Leakage Current	$V_{\text{DS}}=-80\text{V}, V_{\text{GS}}=0\text{V}$	-	-	-25	$\text{\mu A}$
$I_{\text{GSS}}$	Gate-Source Leakage	$V_{\text{GS}}=+20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	+100	nA
$Q_g$	Total Gate Charge	$I_{\text{D}}=-18\text{A}$	-	50	80	nC
$Q_{\text{gs}}$	Gate-Source Charge	$V_{\text{DS}}=-80\text{V}$	-	7.5	-	nC
$Q_{\text{gd}}$	Gate-Drain ("Miller") Charge	$V_{\text{GS}}=-10\text{V}$	-	16.5	-	nC
$t_{\text{d}(\text{on})}$	Turn-on Delay Time	$V_{\text{DS}}=-50\text{V}$	-	12	-	ns
$t_r$	Rise Time	$I_{\text{D}}=-18\text{A}$	-	33	-	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time	$R_{\text{G}}=3.3\Omega$	-	61	-	ns
$t_f$	Fall Time	$V_{\text{GS}}=-10\text{V}$	-	78	-	ns
$C_{\text{iss}}$	Input Capacitance	$V_{\text{GS}}=0\text{V}$	-	2580	4130	pF
$C_{\text{oss}}$	Output Capacitance	$V_{\text{DS}}=-25\text{V}$	-	185	-	pF
$C_{\text{rss}}$	Reverse Transfer Capacitance	f=1.0MHz	-	140	-	pF

## Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{\text{SD}}$	Forward On Voltage <sup>2</sup>	$I_{\text{S}}=-18\text{A}, V_{\text{GS}}=0\text{V}$	-	-	-1.3	V
$t_{\text{rr}}$	Reverse Recovery Time	$I_{\text{S}}=-18\text{A}, V_{\text{GS}}=0\text{V},$ $dI/dt=-100\text{A}/\mu\text{s}$	-	53	-	ns
$Q_{\text{rr}}$	Reverse Recovery Charge		-	125	-	nC

## Notes:


1. Pulse width limited by Max. junction temperature.
2. Pulse test
3. Ensure that the junction temperature does not exceed  $T_{\text{Jmax}}$ .

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.


USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.


APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.




**Fig 1. Typical Output Characteristics**




**Fig 2. Typical Output Characteristics**




**Fig 3. On-Resistance v.s. Gate Voltage**









**Fig 4. Normalized On-Resistance v.s. Junction Temperature**



**Fig 5. Forward Characteristic of Reverse Diode**



**Fig 6. Gate Threshold Voltage v.s. Junction Temperature**





**AP30P10GI**

## **MARKING INFORMATION**

