

JRC-19F(4078)

Contact specification

Contact form	2Z
Contact resistance	≤100mΩ (1A 6VDC)
Contact material	AgCdO AgSnO ₂
Contact capacity	1A 125VDC 2A 30VADC

Coil specification

Rated coil power	360mW
------------------	-------

Coil data


Nominal voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω ± 10%
3	2.25	0.3	25
5	3.75	0.5	70
6	4.5	0.6	100
9	6.8	0.9	225
12	9.0	1.2	400
15	11.3	1.5	625
24	18.0	2.4	1600
48	36.0	4.8	4000



JRC-19F(4078)

Technical specification

Insulation resistance	≥100MΩ (500VDC)
Dielectric strength	Between coil and contacts ≥1000VAC 1min
	Between open contacts ≥1000VAC 1min
	Between contacts of different poles ≥1000VAC 1min
Operate / Release time	≤6ms/4ms
Terminal type	PCB mounting



Outline dimension、 Mounting holes (Bottom view)、 Wiring diagram (Bottom view)

JRC-19F(4078) Outline dimension

JRC-19F(4078) Mounting holes (Bottom view)

JRC-19F(4078) Wiring diagram (Bottom view)